

Blower Enclosures

Reduce noise levels significantly, while protecting the blower from water, dirt and other environmental factors, and from cleaning chemicals during washdown.

Designed for durability and ease of maintenance, Paxton's washdown-duty acoustical blower enclosures protect the blower from harsh environments. The rugged polypropylene enclosure reduces sound levels to within OSHA standards; and the design has no crevices that can hold moisture, greatly reducing the potential for bacteria to grow.

- Protect in harsh, corrosive and wet environments
- Significant sound abatement
- Simplify blower installation and maintenance
- Maintain lower blower temperature for optimum performance





- Reduce noise levels
- Protect blower from dirt, water, corrosivity
- Optimize blower temperature & performance



Air Systems designed and engineered by Paxton Products come with a 100% Performance Guarantee and a best-inclass 3 year warranty on AT- and XT-series blowers

Durable & Functional

- Welded Polypropylene Enclosure
- Stainless Steel base
- Oversized access doors for easy servicing

Proceed to the factor of the f Model Model No. XT-300 XT-500 AT-700 AT-800 AT-1200 PureAir Direct Drive Polypropylene Cabinet Top discharge Bottom discharge Side discharge 3 inch discharge 4 inch discharge Clear access doors (2) Positive seal, fast lock fasteners Full weld construction base, 304 stainless steel Washable expanded aluminum mesh pre-filter Height 28.2 48 28 48 in 716 1219 711 1219 1016 mm 26 35 35 40 20.5 Depth in 889 889 1016 660 521 mm 23.5 22 42 42 16 Width 597 559 1067 1067 406 mm

Features:

- ➤ AT-series enclosures include removeable, reusable, and washable mesh pre-filters that trap larger airborne particulates, extending the service life of the blower inlet filter
- Oversized clear Lexan access doors for easy servicing: no need to disturb ducting to inspect or service the blower
- > Available in 4" and 24" high base models
- > Shipped with blower pre-mounted to allow quick, turnkey installation
- Strong, polypropylene enclosure withstands harsh, wet and corrosive environments
- > No crevices to hold moisture
- > Designed for movement and placement by fork lift
- > Swivel style (adjustable) leveling feet with anchoring holes
- > Half turn, fast-lock access door fasteners
- > O-ring sealed sanitary discharge pipe, 3 or 4 inches
- Durable 304 stainless steel base



Low Profile Base Enclosures



ITW Air Management

10125 Carver Road Cincinnati, OH 45242

Paxton Products...leading the science of high performance drying.

Call +1 800-441-7475 (U.S. & Canada) or +1 513-891-7474 (Worldwide)

Or get an online "Quick-Quote" at paxtonproducts.com









